

# Product Information Sheet

## THREADED ROD, INCH SERIES

**Typical Material:** Low Carbon Steel

**Material and Mechanical Properties:** Purchased to meet ASTM A307 Grade A

**Zinc Plating:** Purchased to meet ASTM F1941 FeZn3A

**Hot-Dip Galvanized:** Purchased to meet ASTM A153

**Threads:** Commercial nut fit similar to Class 1A.

**Typical Hardness:** HRB 70-100

**Tensile Strength:** 60,000 PSI Min



TENSILE STRENGTH -NC THREADS			TENSILE STRENGTH -NF THREADS		
Size	PSI	Pounds	Size	PSI	Pounds
1/4-20	60,000	1900	1/4-28	60,000	2180
5/16-18	60,000	3100	5/16-24	60,000	3480
3/8-16	60,000	4650	3/8-24	60,000	5270
7/16-14	60,000	6350	7/16-20	60,000	7120
1/2-13	60,000	8500	1/2-20	60,000	9600
9/16-12	60,000	11,000	9/16-18	60,000	12,150
5/8-11	60,000	13,550	5/8-18	60,000	15,350
3/4-10	60,000	20,050	3/4-16	60,000	22,400
7/8-9	60,000	27,700	7/8-14	60,000	30,500
1-8	60,000	36,350	1-12	60,000	39,800
1 1/8-7	60,000	45,800	1-14	60,000	40,700
1 1/4-7	60,000	58,150	1 1/8-12	60,000	51,400
1 3/8-6	60,000	69,300	1 1/4-12	60,000	64,400
1 1/2-6	60,000	84,300	1 3/8-12	60,000	78,900
1 3/4-5	60,000	114,000	1 1/2-12	60,000	94,900
2-4 1/2	60,000	150,000			



**GLASER & ASSOCIATES, INC.**

4808 SUNRISE DRIVE, MARTINEZ, CA 94553

TOLL FREE: (855)532-2658 • [WWW.GLASERBOLT.COM](http://WWW.GLASERBOLT.COM)

The information presented is believed to be accurate at the time of document creation. However, Glaser & Associates is not responsible for any claim traceable to any errors (typographical or otherwise) as contained herein. Glaser & Associates makes no warranties as to the accuracy of this information.